

## Plinth elements for wooden and wood-metal balcony doors

### Product description

Frinorm rot-resistant plinth elements for wooden and wood-metal balcony doors for floors are especially suited for a wide range of demands, such as thermal protection and a high load capacity. They are available with rot-resistant cement-bonded chipboard, coated with white primer. Intensely expanded rigid polystyrene foam (EPS perimeter), 30 kg/m<sup>3</sup>, is used for thermal insulation. All possible CNC edge profile work is performed on all sides according to your profile specifications.



### Range and design

Type	Cover panel and surface	Thermal insulation	U-values
Rot-resistant	Both sides 10 mm, cement-bonded chipboard, coated with white primer	Intensely expanded rigid polystyrene foam (EPS perimeter), 30 kg/m <sup>3</sup>	Thermal transmittance coefficients up to 0.3 W/m <sup>2</sup> K  (For U-values, see table on technical data sheet)

### Thicknesses

Thicknesses from 40 mm to 99 mm can be produced.

For thicknesses as from 100 mm, see plinth elements for wooden and wood-metal lifting sliding doors.

### Formats

All formats from 545 × 95 mm to 3338 × 1244 mm can be produced.

### CNC edge milling

All possible CNC edge profile work is performed on all sides according to your profile specifications.

### Consultation

For more information please refer to the technical data sheets. Our technical consultants are at your service for all questions.

### Frinorm AG, Wärmedämmelemente

Föhrenweg 9, FL-9496 Balzers, phone 00423 384 23 66, fax 00423 384 23 35, [www.frinorm.com](http://www.frinorm.com), [info@frinorm.com](mailto:info@frinorm.com)