

Substructure elements for wooden and wood-metal balcony doors

Product description

Frinorm rot-resistant plinth elements for wooden and wood-metal balcony doors for floors are especially suited for a wide range of demands, such as thermal protection and a high load capacity. They are available with a rot-resistant cement-bonded chipboard, coated with white primer. Intensely expanded rigid polystyrene foam (EPS perimeter), 30 kg/m³, is used for thermal insulation. All possible CNC edge profile work is performed on all sides according to your profile specifications.



Range and design

Type	Cover panel and surface	Thermal insulation	U-values
Rot-resistant	Both sides 10 mm, cement-bonded chipboard, coated with white primer	Intensely expanded rigid polystyrene foam (EPS perimeter), 30 kg/m ³	Thermal transmittance coefficients up to 0.3 W/m ² K (For U-values, see table on technical data sheet)

Thicknesses

Thicknesses from 40 mm to 99 mm can be produced.

For thicknesses as from 100 mm, see substructure elements for wooden and wood-metal lifting sliding doors.

Formats

All formats from 545 × 95 mm to 3338 × 1244 mm can be produced.

CNC edge milling

All possible CNC edge profile work is performed on all sides according to your profile specifications.

Consultation

For more information please refer to the technical data sheets. Our technical consultants are at your service for all questions.

Frinorm AG, Wärmedämmelemente

Föhrenweg 12, FL-9496 Balzers, phone 00423 384 23 66, fax 00423 384 23 35, www.frinorm.com, info@frinorm.com