

**Substructure elements for lifting sliding doors
Resistant to moisture and mildew**

Cover panel and surface	Polyurethane recycled board, PH, 26 mm
Thermal insulation	Intensely expanded polystyrene rigid foam (EPS perimeter), 30 kg/m ³ , 48–188 mm
Bonding/adhesive bonding	Water-resistant D3 (EN 204-D3)
Edge preparation/processing	All possible CNC edge profile work is performed according to your threshold profile
Thicknesses	All thicknesses from 100 mm to 240 mm can be produced For thicknesses under 100 mm, see substructure elements for windows and doors
Dimensions	All dimensions from 500 × 95 mm to 3588 × 1294 mm can be produced

Element thicknesses from 100 mm to 240 mm can be produced. For further U-value calculations, please contact our consultants.

Element thickness	mm	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240
Cover panel thickness	mm	26	26	26	26	26	26	26	26	26	26	26	26	26	26	26
Thermal insulation thickness	mm	48	58	68	78	88	98	108	118	128	138	148	158	168	178	188
U-value	W/m²K	0.433	0.383	0.343	0.311	0.284	0.262	0.242	0.226	0.211	0.199	0.187	0.177	0.168	0.160	0.153
Weight	kg/m ²	30.04	30.34	30.64	30.94	31.24	31.54	31.84	32.14	32.44	32.74	33.04	33.34	33.64	33.94	34.24